

AXE5400 Whole Home Mesh Wi-Fi 6E AP

MODEL: HX716 Pro



Overview

HX716 Pro is a high-performance Wi-Fi 6E Tri-band mesh AP with one 2.5Gbps WAN/LAN port and two gigabit LAN ports. Deliver even more faster Wi-Fi speeds with less interference and congestion while being backwards compatible with 802.11a/b/g/n/ac Wi-Fi devices. Perfect for FTTH deployment and a fully connected home.



AXE5400 Tri-Band Wi-Fi

Deliver total Wi-Fi speeds up to 5.4 Gbps across 6 GHz, 5 GHz, and 2.4 GHz bands for even faster speeds, lower latency, and better online experience.



Works on 6 GHz Band

Minimize congestion with greenfield spectrum to enable high-bandwidth applications that require faster data throughput.



2.5G Wired Connection

Take full use of the bandwidth speeds to 2.5 Gbps throgh one 2.5Gbps WAN/LAN port for even faster internet access and wired connection.



Easy Remote Management

TR-069 and TR-369 protocols, Aginet app, and TAUC (TP-Link Aginet Unified Cloud) are supported, service providers can manage multiple devices remotely.



Specifications

Hardware

Interface

1× 10/100/1000/2500 Mbps RJ45 WAN/LAN Port, 2× 10/100/1000 Mbps RJ45 LAN Ports,

Antenna

Internal Wi-Fi antennas

• External Power Supply

12VDC/2.0A

• Dimensions (W * D * H)

4.1 × 4.1 × 6.7 in (105 × 105 × 169 mm)

• Button

Reset Button, WPS Button

• CPU

1 GHz ARM Dual-Core CPU

Wireless

• Wireless Standards

IEEE 802.11ax 6GHz, IEEE 802.11a/n/ac/ax 5GHz, IEEE 802.11b/g/n/ax 2.4GHz

Mesh Protocol

802.11k/v/r

Frequency

2.4GHz, 5GHz, and 6GHz

• Signal Rate

574 Mbps on 2.4GHz, 2402 Mbps on 5GHz, 2402 Mbps on 6GHz

• Transmit Power

CE: <20dBm (2.4GHz); <23dBm (5GHz); <23dBm (6GHz) FCC: <30dBm (2.4GHz); <30dBm (5GHz); <30dBm (6GHz)

· Wireless Security

WPA/WPA2/WPA3 Personal

• Wireless Function

Enable/Disable Wireless Radio, WMM, Wireless Statistics, Multi-SSID, Guest Network, TX Beamforming

Wireless Schedule

Supports 2.4 GHz, 5 GHz, and 6 GHz Wireless Schedule

EasyMesh Support

Seamless Roaming, Self-healing, 80211k/v/r Support

Software

· Working Mode

Router Mode, Access Point Mode

• WAN Type

Dynamic IP/Static IP/PPPoE/PPTP/L2TP/Bridge

Protocols

Supports IPv4 and IPv6

• Multi SSID

Up to 3 SSIDs for each band (including main SSID)

Features

Parental Control, QoS (Quality of Service), Address Reservation, Port Forwarding, Cloud Firmware Upgrade, Firewall, Network Diagnostic, CWMP, Traffic Statistic, 1024-QAM, MU-MIMO, OFDMA

Management

Local management: WebGUI management, Aginet app management Remote management: TR-069, TR-181, TR-369, TR-111,TR-143 Cloud management: TAUC

• DHCP

Server, DHCP Client List, Address Reservation

Port Forwarding

Virtual Server, Port Triggering, UPnP, DMZ

Dynamic DNS

NO-IP, DynDNS

VPN Server

PPTP, OpenVPN, IPSec

VPN Pass-through

IPSec, PPTP, L2TP

· Access Control

Parental Control, Local Management, Host List, White/Black List

Firewall Security

DoS, SPI Firewall, IP and MAC Address Binding

Others

• System Requirements

Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, 8, 8.1,10, MAC OS, NetWare, UNIX or Linux Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0 browers or higher.

· Certifications

FCC, CE

Environment

Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~60°C (-40°F~140°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

Package Contents

AXE5400 Whole Home Mesh Wi-Fi 6E AP HX716 Pro

1× RJ45 Ethernet Cable

1× Power Adapter

1× Quick Installation Guide