

## UniFi LTE Backup Professional



## Mechanical

Dimensions	66 x 202 x 32 mm (2.6 x 7.95 x 1.26")
Weight	Without stand: 223 g (7.86 oz) With stand: 336 g (11.85 oz)
Enclosure material	Polycarbonate
Mount material	Stand: aluminum Wall mount: polycarbonate

## Hardware

Networking interface	(2) GbE RJ45 ports LTE Category 4 radio
Management interface	Ethernet
PoE interface	(1) PoE in (PoE output not used) (1) PoE passthrough output (requires a PoE+ switch)
SIM	Nano SIM
LTE bands	Band 2, 4, 5, 12, 14, 66
Operator	AT&T network
Power supply	UniFi PoE switch 48V, 0.5A PoE adapter
Supported voltage range	44–57V DC
Max. power consumption	Excluding PoE passthrough output: 8.5W
Max. PoE passthrough wattage per port	15.4W* <small>*Requires a PoE+ switch</small>
MIMO	2 x 2 LTE Category 4
Throughput speeds*	Download 150 Mbps / Upload 50 Mbps <small>*Speed and coverage depend on location and network performance.</small>
Antenna	(2) Internal LTE antennas (1) Female RP-SMA connector for an external antenna (optional)* <small>*The maximum antenna gain must not exceed 6dBi to comply with regulation.</small>
External antenna port*	Female RP-SMA connector <small>*Please use male RP-SMA antennas to match the ULTEBackup Pro.</small>
LCM display	1.54" screen
Button	Factory-reset
Mounting	Wall mount/foot stand (included)
Operating temperature	-10 to 60° C (-14 to 140° F)
Operating humidity	5 to 95% noncondensing
Certifications	FCC, IC

