

Model: PE10G

10 Gbps PCI-E Ethernet Adapter





Highlights

Single-port, high-speed 10GBASE-T/NBASE-T NIC for bandwidth-demanding PC and servers.

- 10 Gbps Ethernet Ports
- 10G/5G/2.5G/1G/100M/10M
- Wake on LAN, Flow Control
- Windows PC, Mac, Synology NAS, etc
- Windows, Linux, DSM 7.2+ etc

Package Content

- PE10G
- Low-Profile Bracket
- Installation Guide
- 1.5 m Ethernet Cable

Hardware Features

CPU	Chipset	Marvell AQC113
Interfaces	10G RJ45 Ports	1
	LED	Speed/Link/ACT of Ethernet Port
Requirements	Hardware Requirement	Requires a PCI-E 3.0 x4 or higher slot on the motherboard for powering and the Ethernet function.
	Compatible OS	Windows 7/8/8.1/10/11
		WindowsServer 2008R2~2022
		Linux
		DSM 7.2+
	Driver Installation	Manual driver installation is required.
Driver is available from the Download Center.		
Driver-free on DSM7.2+.		
Reliability	Environment	Ambient Operating Temperature:
		0 °C ~ 70 °C (32 °F ~158 °F)
		Storage Temperature:
		-40 °C ~ 70 °C (-40 °F ~ 158 °F)
		Humidity: 10% ~ 90% non-condensing
		Storage Humidity: 5% ~ 95% non-condensing
Certifications	FCC, CE	